


Aufhängeglied mit Gabel Typ AG
entspricht EN 1677-4
rot lackiert

Clevis type master link type AG
acc. to EN 1677-4
red varnished



Nenngröße nominal size	Tragfähigkeit WLL kg	b mm	c mm	d ₁ mm	d ₂ mm	h mm	l mm	s mm	t mm	w mm	Gewicht per Stk. kg weight per pc. kg	Artikelnummer stock no.
6-8	1120	6,5	32	8	13	103	160	18	133	60	0,5	207 680 006
7-8	1500	7,5	36	8,8	15	102	164	21	133	58	0,6	207 680 007
8-8	2000	9	40	10	16	105	172	23	138	60	0,7	207 680 008
10-8	3150	12	50	12	18	128	207	25	167	75	1,1	207 680 010
13-8	5300	15	60	16	22	150	254	35	203	90	2,0	207 680 013
16-8	8000	17	75	20	26	165	292	41	230	100	3,6	207 680 016




**Endglied Typ EG DIN 5688-3
mit Abflachung**
entspricht EN 1677-4
rot lackiert

**Sub and end link type EG acc. to DIN 5688-3
with flat part**
acc. to EN 1677-4
red varnished



Nenngröße nominal size	Tragfähigkeit WLL kg	d mm	l mm	w mm	Gewicht per Stk. kg weight per pc. kg	Artikelnummer stock no.
6-8	1120	13	60	30	0,2	209 512 006
7-8	1500	16	70	35	0,4	209 512 007
8-8	2000	16	70	35	0,4	209 512 008
10-8	3150	20	90	45	0,7	209 512 010
13-8	5300	26	120	60	1,6	209 512 013
16-8	8000	28	130	65	1,9	209 512 016
18/20-8	12500	32	140	70	2,9	209 512 018



Wichtiger Hinweis

Derzeit stellen wir unser Lager auf die neue Ausgabe der Norm DIN 5688-3:2007-04 um. Die alten Bestände nach DIN 5688-3:1986-07 werden ausverkauft.

Important note

Actually, we are changing our stocks to the new edition of the standard DIN 5688-3:2007-04. The stocks according to DIN 5688-3:1986-07 are available while stocks last.

