


Ringmutter DIN 582:2003-08
aus C 15E
verzinkt

Eye nut acc. to DIN 582:2003-08
made of C 15E
galvanized

Nenngröße nominal size	Tragfähigkeit in geradem Zug kg WLL in straight pull kg	d ₂ mm	d ₃ mm	d ₄ mm	h mm	Gewicht per Stk. kg weight per pc. kg	Artikelnummer stock no.
M 6*	-	20	36	20	34	0,1	106 055 006
M 8	140	20	36	20	36	0,1	106 055 008
M 10	230	25	45	25	45	0,1	106 055 010
M 12	340	30	54	30	53	0,2	106 055 012
M 16	700	35	63	35	62	0,2	106 055 016
M 20	1200	40	72	40	71	0,4	106 055 020
M 24	1800	50	90	50	90	0,7	106 055 024
M 30	3200	65	108	60	109	1,3	106 055 030




* Nenngröße M 6 nicht nach DIN.

* Nominal size M 6 not acc. to DIN.

Ringschraube DIN 580:2003-08
aus C 15E
verzinkt

Eye bolt acc. to DIN 580:2003-08
made of C 15E
galvanized

Nenngröße nominal size	Tragfähigkeit in geradem Zug kg WLL in straight pull kg	d ₂ mm	d ₃ mm	d ₄ mm	h mm	L mm	Gewicht per Stk. kg weight per pc. kg	Artikelnummer stock no.
M 6*	-	20	36	20	47	13	0,1	106 057 006
M 8	140	20	36	20	49	13	0,1	106 057 008
M 10	230	25	45	25	63	17	0,1	106 057 010
M 12	340	30	54	30	73,5	20,5	0,2	106 057 012
M 16	700	35	63	35	89	27	0,3	106 057 016
M 20	1200	40	72	40	101	30	0,4	106 057 020
M 24	1800	50	90	50	126	36	0,8	106 057 024
M 30	3200	65	108	60	154	45	1,7	106 057 030



* Nenngröße M 6 nicht nach DIN.

* Nominal size M 6 not acc. to DIN.

