


**Ösenhaken** früher DIN 689 (Ausgabe Mai 1944)  
mit Sicherung, roh

**Eye hook** previously DIN 689  
with safety latch, self-coloured


Tragfähigkeit WLL kg	b mm	d mm	l mm	m <sub>2</sub> mm	s mm	t mm	Gewicht per Stk. kg weight per pc. kg	Artikelnummer stock no.
250	12	7,5	88	15	13	64	0,2	133 431 002
500	16	10	117	21	17	85	0,4	133 431 005
1000	20	13,5	160	30	23,5	116	0,8	133 431 010
1600	26	16	190	36	28	138	1,4	133 431 016
2500	32	20	240	46	35	174	2,9	133 431 025



**Ösenhaken** früher DIN 689 (Ausgabe Mai 1944)  
ohne Sicherung, roh

**Eye hook** previously DIN 689  
without safety latch, self-coloured

Tragfähigkeit WLL kg	b mm	d mm	l mm	m <sub>1</sub> mm	s mm	t mm	Gewicht per Stk. kg weight per pc. kg	Artikelnummer stock no.
250	12	7,5	88	18	13	64	0,2	133 430 002
500	16	10	117	24	17	85	0,4	133 430 005
1000	20	13,5	160	33	23,5	116	0,8	133 430 010
1600	26	16	190	39	28	138	1,4	133 430 016
2500	32	20	240	49	35	174	2,9	133 430 025




**Wichtiger Hinweis:** Ösenhaken DIN 689 sind für sicherheitstechnische Anwendungen nicht geeignet.  
Die Haken sind aus nicht alterungsbeständigem Material gefertigt.

**Important note:** Eye hooks acc. to DIN 689 are not suitable for safety applications.  
The hooks are made of material which is not resistant to age.


**Abschlepphaken**  
verzinkt

**Grab hook**  
galvanized


Bruchlast* kg breaking load limit* kg	b mm	d mm	l mm	m mm	s mm	t mm	Gewicht per Stk. kg weight per pc. kg	Artikelnummer stock no.
2000	18	9	91	10	12	66	0,2	134 233 020
2500	20	7	105	14	14	77	0,2	134 233 025
3500	18	8	91	13	12	65	0,2	134 233 035



2 t



2,5 t



3,5 t

\* Bitte Bruchlast nicht mit Tragfähigkeit verwechseln.  
\* These are breaking load limits not working load limits.